



Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07

Date of issue: 01/14/2026

Revised on 01/14/2026

1 Identification

- **Product Identifier**
- **Trade Name: Denatured Fuel Grade Ethanol**
- **Relevant identified uses of the substance or mixture and uses advised against:**
- **Product Description:** Fuel Ethanol, E98, Denatured ethanol
- **Details of the Supplier of the Safety Data Sheet:**
- **Manufacturer/Supplier:**
Husker Ag LLC.
54048 Hwy 20
Plainview, NE 68769
(402) 582-4446
- **Emergency telephone number:**
Chemtrec (US and Canada): (800) 424-9300
Chemtrec (Outside US): +1 (703) 527-3887 (Collect calls accepted)

* 2 Hazard(s) Identification

- **Classification of the substance or mixture:**



Flame

Flammable liquids 2

H225 Highly flammable liquid and vapor.



Health hazard

Germ cell mutagenicity 1B

H340 May cause genetic defects.

Carcinogenicity 2

H351 Suspected of causing cancer.

Aspiration hazard 1

H304 May be fatal if swallowed and enters airways.



Eye irritation 2A

H319 Causes serious eye irritation.

Specific target organ toxicity (single exposure) 3

H335 May cause respiratory irritation.

- **Label elements:**
- **Hazard pictograms:**



- **Signal word:** Danger

- **Hazard-determining components of labeling:**

Ethanol

Gasoline, natural

- **Hazard statements:**

H225 Highly flammable liquid and vapor.

H319 Causes serious eye irritation.

H340 May cause genetic defects.

H351 Suspected of causing cancer.



Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07

Date of issue: 01/14/2026

Revised on 01/14/2026

Trade Name: Denatured Fuel Grade Ethanol

H335 May cause respiratory irritation.
H304 May be fatal if swallowed and enters airways.

Precautionary statements:

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P240 Ground / bond container and receiving equipment.
- P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
- P242 Use non-sparking tools.
- P243 Take action to prevent static discharge.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
- P264 Wash thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
- P301+P310 If swallowed: Immediately call a poison center/doctor.
- P331 Do NOT induce vomiting.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P312 Call a poison center/doctor if you feel unwell.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P370+P378 In case of fire: Use CO2, powder or water spray to extinguish.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Unknown acute toxicity:


This value refers to knowledge of known, established toxicological or ecotoxicological values.
0 % of the mixture consists of component(s) of unknown toxicity.

Information pertaining to particular dangers for man and environment:

- **Classification system:** NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme
- **NFPA ratings (scale 0 - 4)**



HMIS-ratings (scale 0 - 4)



- **Hazard(s) not otherwise classified (HNOC):** None known

Classification according to (d)(1)(ii) of § 1910.1200

The SDS issuer does not object to the classifications provided by importers or manufacturers of precursor products.



Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07

Date of issue: 01/14/2026

Revised on 01/14/2026

Trade Name: Denatured Fuel Grade Ethanol

Hazards not otherwise classified

There are no adverse physical or health effects known that are not covered by the hazard classes of the Hazard Communications Standard.

3 Composition/Information on Ingredients

Chemical characterization: Substance**Description:**

Mixture of substances listed with non-hazardous additions and/or components that are less than listing threshold. All non-hazardous, components listed under threshold, and listed component total 100%.

Dangerous Components:

CAS: 64-17-5 RTECS: KQ 6300000	Ethanol ⚠ Flammable liquids 2, H225; ⚠ Eye irritation 2A, H319; Specific target organ toxicity (single exposure) 3, H335	95-98%
CAS: 8006-61-9 RTECS: LX3300000	Gasoline, natural ⚠ Flammable liquids 2, H225; ⚠ Germ cell mutagenicity 1B, H340; Carcinogenicity 2, H351; Aspiration hazard 1, H304; ⚠ Eye damage 1, H318; ⚠ Skin irritation 2, H315	2-5%

Additional information:

The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of §1910.1200 of 29 CFR 1910.1200 Trade Secrets.

* 4 First-Aid Measures

Description of first aid measures

General information: If symptoms persist, call a physician.

After inhalation: In case of unconsciousness place patient stably in the side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation occurs, consult a doctor.

After eye contact:

Rinse opened eye for at least 15 minutes under running water. If symptoms persist, consult a doctor.

If easy to do so, remove contact lenses if worn.

If eye irritation occurs, consult a doctor.

After swallowing:

Never give anything by mouth to an unconscious person.

Seek immediate medical attention.

To prevent aspiration of swallowed product, lay victim on side with head lower than waist.

May be harmful if ingested. Can cause respiratory depression and could be fatal. Call a physician or poison control center immediately.

If swallowed and symptoms occur, consult a doctor.

Most important symptoms and effects, both acute and delayed:

Harmful if swallowed. Aspiration hazard if swallowed. Can enter lungs and cause damage. Irritating to mouth, throat and stomach.

Dizziness

Nausea

Indication of any immediate medical attention and special treatment needed:

If swallowed or in case of vomiting, danger of entering the lungs.

(Contd. on page 4)



Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07

Date of issue: 01/14/2026

Revised on 01/14/2026

Trade Name: Denatured Fuel Grade Ethanol

* 5 Fire-Fighting Measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** No further relevant information.
- **Special hazards arising from the substance or mixture:**
Do not use a solid water stream as it may scatter and spread fire.
Cool closed containers exposed to fire with water spray.
Flash back possible over considerable distance.
May form explosive mixtures in air.
Exposure to decomposition products may be a hazard to health.
Carbon oxides
- **Advice for firefighters**
- **Special protective equipment for firefighters:**
As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

* 6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures:**
Keep away from ignition sources
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Dilute with plenty of water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (i.e. sand, diatomite, acid binders, universal binders, sawdust).
Dispose of contaminated material as waste according to section 13.
Ensure adequate ventilation.
Dispose of the collected material according to regulations.

· PAC-1:		
64-17-5	Ethanol	1800 ppm
· PAC-2:		
64-17-5	Ethanol	3300* ppm
· PAC-3:		
64-17-5	Ethanol	15000* ppm

- **Reference to other sections:**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

* 7 Handling and Storage

- **Precautions for safe handling:**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect from heat.



Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07

Date of issue: 01/14/2026

Revised on 01/14/2026

Trade Name: Denatured Fuel Grade Ethanol

Protect against electrostatic charges.
Keep protective respiratory device available.

· **Conditions for safe storage, including any incompatibilities**

· **Storage**

· **Requirements to be met by storerooms and receptacles:**

Keep away from any sources of heat or flame.

Store in a cool, dry place.

Do not store in direct sunlight.

Store in a cool location.

Store in the original container.

· **Information about storage in one common storage facility:** Store away from oxidizing agents.

· **Further information about storage conditions:**

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· **Specific end use(s):** Fuel

* 8 Exposure Controls/Personal Protection

· **Control parameters:**

· **Components with occupational exposure limits:**

64-17-5 Ethanol

PEL Long-term value: 1900 mg/m³, 1000 ppm

REL Long-term value: 1900 mg/m³, 1000 ppm

TLV Short-term value: 1880 mg/m³, 1000 ppm
A3

8006-61-9 Gasoline, natural

REL See Pocket Guide App. A

TLV Short-term value: 1480 mg/m³, 500 ppm
Long-term value: 890 mg/m³, 300 ppm
bulk handling

· **Additional information:** The lists that were valid during the creation of this SDS were used as basis.

· **Exposure controls:**

· **Appropriate engineering controls** No further data; see section 7.

· **Personal protective equipment**

· **General protective and hygienic measures:**

Do not eat, drink, smoke or sniff while working.

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· **Breathing equipment:**



NIOSH/OSHA or EN approved respiratory protection is recommended for use in airborne concentrations exceeding exposure limits.



Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07

Date of issue: 01/14/2026

Revised on 01/14/2026

Trade Name: Denatured Fuel Grade Ethanol**Protection of hands:**

Protective gloves

- **Material of gloves:** Chemical resistant
- **Penetration time of glove material:** Not applicable.
- **Eye protection:**



Tightly sealed goggles

- **Body protection:** Flame resistant clothing
- **Limitation and supervision of exposure into the environment:** None

*** 9 Physical and Chemical Properties****Information on basic physical and chemical properties****General Information**

· Physical state	Liquid
· Color:	Clear
· Odor:	Alcohol-like
· Odor threshold:	Not determined
· Melting point/Melting range:	Not determined.
· Boiling point/Boiling range:	≥78 °C (≥172.4 °F)
· Flammability:	Highly flammable.
· Explosion limits:	
· Lower:	3.3 Vol %
· Upper:	19 Vol %
· Flash point:	<0 °C (<32 °F)
· Auto igniting:	≥425 °C (≥797 °F)
· Decomposition temperature:	Not determined
· pH-value @ 20 °C (68 °F):	7.6
· Viscosity:	
· Kinematic:	Not determined
· Dynamic:	Not determined
· Solubility in / Miscibility with:	
· Water:	Fully miscible.
· Partition coefficient (n-octanol/water):	Not determined
· Vapor pressure @ 20 °C (68 °F):	≤59 hPa (≤44.3 mm Hg)
· Vapor pressure @ 50 °C (122 °F):	≤280 hPa (≤210 mm Hg)
· Density @ 20 °C (68 °F):	0.7879 g/cm ³ (6.575 lbs/gal)
· Relative density:	Not determined
· Vapor density @ 20 °C (68 °F):	1.6 (Heavier than air)
· Particle characteristics	Not applicable
· Other information:	
· Appearance:	
· Form:	Liquid

(Contd. on page 7)



Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07

Date of issue: 01/14/2026

Revised on 01/14/2026

Trade Name: Denatured Fuel Grade Ethanol**· Important information on protection of health and environment, and on safety.****· Ignition temperature:**

Product is not self-igniting.

· Danger of explosion:

Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Solvent content:**· Organic solvents:**

97.0 %

· VOC content:

97.00 %

764.3 g/l / 6.38 lb/gal

· Solids content:

0.0 %

· Change in condition**· Evaporation rate:**

Not determined

10 Stability and Reactivity

· Reactivity: The product is stable at ambient temperature and under normal conditions of use.**· Chemical stability:** Product is stable under normal conditions.**· Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.**· Possibility of hazardous reactions:** No dangerous reactions known.**· Conditions to avoid:**

Extremes of temperature and direct sunlight.

Avoid all sources of ignition: heat, sparks and open flames.

Heat, flame and ignition sources.

· Incompatible materials:

Strong oxidizing agents, acids, alkali metals, ammonia, hydrazine, peroxides, sodium, acid anhydrides, calcium hypochlorite, chromyl chloride, nitrosyl perchlorate, bromine pentafluoride, perchloric acid, silver nitrate, mercuric nitrate, potassium-tert-butoxide, magnesium perchlorate, acid chlorides, platinum, uranium hexafluoride, silver oxide, iodine heptafluoride, acetyl bromide, disulfuryl difluoride, tetrachlorosilane + water, acetyl chloride, permanganic acid, ruthenium (VIII) oxide, uranyl perchlorate, potassium dioxide.

· Hazardous decomposition products:Under fire conditions this material may produce hazardous carbon dioxide (CO₂), carbon monoxide (CO), various low molecular weight hydrocarbons, and smoke.

Flammable gases/vapors

*11 Toxicological Information

· Information on toxicological effects:**· Acute toxicity:****· LD/LC50 values that are relevant for classification:****64-17-5 Ethanol**

Oral	LD50	7,060 mg/kg (Rat) Remarks: Lungs, Thorax, or Respiration: Other changes. Carcinogenicity - Mouse - Oral Tumorigenic: Equivocal tumorigenic agent by RTECS criteria. Liver: Tumors. Blood: Lymphomas including Hodgkin's disease. Central nervous system depression, narcosis, Damage to the heart., To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated. Heart - Irregularities - Based on Human Evidence Central nervous system - Breathing difficulties - Based on Human Evidence Stomach - Irregularities - Based on Human Evidence
Inhalative	LC50/4 h	20,000 mg/l (Rat)

(Contd. on page 8)



Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07

Date of issue: 01/14/2026

Revised on 01/14/2026

Trade Name: Denatured Fuel Grade Ethanol

	LC50/96 hours	12,900-15,300 mg/l (Trout)
8006-61-9 Gasoline, natural		
Inhalative	LC50/4 h	300 mg/l (Rat)

Primary irritant effect:

- **On the skin:** Irritant to skin and mucous membranes.

- **On the eye:** Irritating effect.

- **Carcinogenicity** Group 2B - Possibly carcinogenic to humans

Reproductive toxicity

May damage fertility. May damage the unborn child. May cause heritable genetic damage.

Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

- Irritant

- Carcinogenic

- The product can cause inheritable damage.

- **Interactive effects** No interactive effects between components are known.

Carcinogenic categories:**IARC (International Agency for Research on Cancer):**

The IARC (the International Agency for Research on Cancer) concluded that ethanol found alcoholic beverages to be Group 1 - Carcinogenic to humans. All other instances it is not consider carcinogenic.

- Group 1 - Carcinogenic to humans

- Group 2A - Probably carcinogenic to humans

- Group 2B - Possibly carcinogenic to humans

- Group 3 - Not classifiable as to its carcinogenicity to humans

- Group 4 - Probably not carcinogenic to humans

64-17-5	Ethanol	1
8006-61-9	Gasoline, natural	2B

NTP (National Toxicology Program):

None of the ingredients are listed.

OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

Alternative sources for toxicological information

No non-standard sources for toxicological information where used.

12 Ecological Information

Toxicity:**Aquatic toxicity:****64-17-5 Ethanol**

EC50 34,900 mg/l (Daphnia)

- **Persistence and degradability:** No further relevant information available.

- **Bioaccumulative potential:** No further relevant information available.

- **Mobility in soil:** No further relevant information available.

Results of PBT and vPvB assessment:

- **PBT:** Not applicable

- **vPvB:** Not applicable

(Contd. on page 9)



Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07

Date of issue: 01/14/2026

Revised on 01/14/2026

Trade Name: Denatured Fuel Grade Ethanol

- **Other adverse effects:**
- **Additional ecological information:**
- **General notes:**

Water hazard class 3 (Self-assessment): extremely hazardous for water
 Do not allow product to reach ground water, water course or sewage system, even in small quantities.
 Danger to drinking water if even extremely small quantities leak into the ground.

* 13 Disposal Considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household waste. Do not allow product to reach sewage system. Observe all federal, state and local environmental regulations when disposing of this material.
- **Waste disposal key:** US EPA RCRA waste code D001 (ignitability characteristic).
- **Uncleaned packaging**
- **Recommendation:** Handle empty containers with care because residual vapors are flammable.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport Information

- **UN-Number:** UN1987
- **DOT, ADR/ADN, IMDG, IATA** UN1987
- **UN proper shipping name:** Alcohols, n.o.s. (Ethanol)
- **DOT** UN1987 ALCOHOLS, N.O.S. (ETHANOL (ETHYL ALCOHOL))
- **ADR/ADN** UN1987 ALCOHOLS, N.O.S. (ETHANOL (ETHYL ALCOHOL))
- **IMDG** ALCOHOLS, N.O.S. (ETHANOL (ETHYL ALCOHOL))
- **IATA** ALCOHOLS, N.O.S. (ETHANOL)
- **Transport hazard class(es):**
- **DOT**



- **Class:** 3 Flammable liquids
- **Label:** 3

· **ADR/ADN**



- **Class:** 3 (F1) Flammable liquids
- **Label:** 3

· **IMDG, IATA**



- **Class:** 3 Flammable liquids
- **Label:** 3



Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07

Date of issue: 01/14/2026

Revised on 01/14/2026

Trade Name: Denatured Fuel Grade Ethanol

- **Packing group:** II
 - **DOT, ADR/ADN, IMDG, IATA** II
 - **Environmental hazards:** Not applicable
 - **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:** Not applicable
 - **Transport/Additional information:**
 - **DOT**
 - **Quantity limitations:** On passenger aircraft/rail: 5 L
On cargo aircraft only: 60 L
-
- **ADR/ADN**
 - **Excepted quantities (EQ):** Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml
-
- **IMDG**
 - **Limited quantities (LQ):** 1L
 - **Excepted quantities (EQ):** Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml
 - **Special precautions for user:** Warning: Flammable liquids
 - **Hazard identification number (Kemler code):** 33
 - **EMS Number:** F-E,S-D
 - **Stowage Category:** B
 - **UN "Model Regulation":** UN 1987 ALCOHOLS, N.O.S. (ETHANOL (ETHYL ALCOHOL)), 3, II

*15 Regulatory Information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture:**
- **SARA (Superfund Amendments and Reauthorization):**

· **Section 355 (extremely hazardous substances):**
None of the ingredients are listed.

· **Section 313 (Specific toxic chemical listings):**
None of the ingredients are listed.

· **TSCA (Toxic Substances Control Act):**
All components have the value ACTIVE.

· **Hazardous Air Pollutants**
None of the ingredients are listed.

· **California Proposition 65:**



WARNING: This product can expose you to chemicals including [one or more listed chemical] which is [are] known to the State of California to cause cancer [or birth defects or other reproductive harm]. For more information, go to www.P65Warnings.ca.gov.

· **Chemicals known to cause cancer:**
None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for females:**
None of the ingredients are listed.



Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07

Date of issue: 01/14/2026

Revised on 01/14/2026

Trade Name: Denatured Fuel Grade Ethanol

· Chemicals known to cause reproductive toxicity for males:		
None of the ingredients are listed.		
· Chemicals known to cause developmental toxicity:		
None of the ingredients are listed.		
· New Jersey Right-to-Know List:		
All ingredients are listed.		
· New Jersey Special Hazardous Substance List:		
64-17-5	Ethanol	CA, MU, TE, F3
8006-61-9	Gasoline, natural	CA, F3
· Pennsylvania Right-to-Know List:		
64-17-5	Ethanol	
· Pennsylvania Special Hazardous Substance List:		
None of the ingredients are listed.		
· Carcinogenic categories:		
· EPA (Environmental Protection Agency):		
None of the ingredients are listed.		
· TLV (Threshold Limit Value established by ACGIH):		
All components have the value A3.		
· NIOSH-Ca (National Institute for Occupational Safety and Health):		
8006-61-9	Gasoline, natural	

· GHS label elements
 The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:



· Signal word: Danger

· Hazard-determining components of labeling:

Ethanol
Gasoline, natural

· Hazard statements:

H225 Highly flammable liquid and vapor.
H319 Causes serious eye irritation.
H340 May cause genetic defects.
H351 Suspected of causing cancer.
H335 May cause respiratory irritation.
H304 May be fatal if swallowed and enters airways.

· Precautionary statements:

P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P240 Ground / bond container and receiving equipment.
 P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
 P242 Use non-sparking tools.



Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07

Date of issue: 01/14/2026

Revised on 01/14/2026

Trade Name: Denatured Fuel Grade Ethanol

P243	Take action to prevent static discharge.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P301+P310	If swallowed: Immediately call a poison center/doctor.
P331	Do NOT induce vomiting.
P303+P361+P353	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P304+P340	If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	If exposed or concerned: Get medical advice/attention.
P312	Call a poison center/doctor if you feel unwell.
P337+P313	If eye irritation persists: Get medical advice/attention.
P370+P378	In case of fire: Use CO ₂ , powder or water spray to extinguish.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

National regulations:

The product is not subject to be labelled according with the prevailing version of the regulations on hazardous substances.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other Information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

Date of previous version 07/27/2021

Version number of previous version: 2

Date of preparation 01/14/2026

Abbreviations and acronyms:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety & Health Administration

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

(Contd. on page 13)



Safety Data Sheet

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2024 and GHS Rev 07

Date of issue: 01/14/2026

Revised on 01/14/2026

Trade Name: Denatured Fuel Grade Ethanol

Flammable liquids 2: Flammable liquids – Category 2

Skin irritation 2: Skin corrosion/irritation – Category 2

Eye damage 1: Serious eye damage/eye irritation – Category 1

Eye irritation 2A: Serious eye damage/eye irritation – Category 2A

Germ cell mutagenicity 1B: Germ cell mutagenicity – Category 1B

Carcinogenicity 2: Carcinogenicity – Category 2

Specific target organ toxicity (single exposure) 3: Specific target organ toxicity (single exposure) – Category 3

Aspiration hazard 1: Aspiration hazard – Category 1

*** Data compared to the previous version altered.**

SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106